

TECHNICAL DATASHEET

STALOC MULTI PROTECTION V7

SQ-470

PRODUCT DESCRIPTION

STALOC multi protection V7 is an excellent lubricant with a wide area of applications. The product can be used to release, lubricate, clean and care for different substrates. It is ideal for use in workshops and industrial applications.

It helps to break away seized or blocked threads and screws, e.g. door closers, hinges, bolts, bushings, bearings, cranks, levers, chains, rods, valves, rudders, blocks, bar guides, bowden cables, axles, cams, etc.

Moreover, the product can be used for fine mechanical applications, gauges, office and workshop equipment, etc.

It prevents corrosion, eliminates moisture and water and aids jump starts of engines.

APPLICATION

Recommended application – further information can be found in the material safety data sheet

Spray STALOC multi protection v7 onto the substrate and provide for enough time for action. The product comes with a capillary tube which ensures, that the product can be laid on areas that are difficult to access.

TECHNICAL PROPERTIES

ATTRIBUTE	UNIT	SPECIFICATION
colour		transparent
chemical basis		combination of mineral oils, solvents and special additives
temperature resistance	°C	-30°C to +230°C

Does not contain silicone, grease or acids. No gumming. Excellent capillary action. Filled with environment-neutral propellant.

SAFETY INFORMATION

Please send your request for the latest version of the material safety data sheet (MSDS).

PACKAGING / VOLUME

400 ml 520 3e / 12 pcs. per box

The information and data in this document are for information purposes only. STALOC cannot take responsibility for the results obtained by a third party, whose methods are not under STALOC control. The determination of the suitability for the user's purpose of any STALOC product is the responsibility of the client. Consequently, STALOC recommends testing of the products before using it for a series application. Moreover, it is the responsibility of the customer to ensure a safe environment for the user. STALOC therefore disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of STALOC products. STALOC cannot be held liable for any consequential or incidental damage resulting from the use of a STALOC product, including lost profits or damages of any other kind. Products or processes mentioned herein might be subject to released or pending patents or licences.

Issued: 04.05.2012

