

TECHNICAL DATASHEET

STALOC RUST KILLER

SQ-625 – SHOCK FREEZE

PRODUCT DESCRIPTION

STALOC RUST KILLER is used to quickly release rust and prevent ongoing corrosion. Can be used for bolts, nuts, screws, Bowden cables, hinges, etc.

The combination of a deep freezing effect and creeping oils make the product essential for all maintenance and repair operations. Its immediate penetration increases efficiency in your operations, thus saves time and money.

APPLICATION

Recommended application – further information can be found in the material safety data sheet.

Apply on parts, allow for 1-2 minutes penetration time. Brush or wipe off rust. If necessary, repeat the operation.

TECHNICAL PROPERTIES

ATTRIBUTE	UNIT	SPECIFICATION
Shock freeze temperature	°C	-40°C
basis		mineral oil
colour		transparent

- does not contain silicone or resins
- does not harm rubber or sealants
- does not leave residues

SAFETY INFORMATION

Please send your request for the latest version of the material safety data sheet (MSDS).

PACKAGING / VOLUME

500 ml 650 3e à 12 pcs. per box

The information and data in this document are for information purposes only. STALOC cannot take responsibility for the results obtained by a third party, whose methods are not under STALOC control. The determination of the suitability for the user's purpose of any STALOC product is the responsibility of the client. Consequently, STALOC recommends testing of the products before using it for a series application. Moreover, it is the responsibility of the customer to ensure a safe environment for the user. STALOC therefore disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of STALOC products. STALOC cannot be held liable for any consequential or incidental damage resulting from the use of a STALOC product, including lost profits or damages of any other kind. Products or processes mentioned herein might be subject to released or pending patents or licences.

Issued: 04.05.2012



call STALOC



www.staloc.com

