

TECHNICAL DATASHEET

STALOC KORROTECH 2000 HIGH PERFORMANCE PROTECTIVE OIL

SQ-1002

PRODUCT DESCRIPTION

STALOC KORROTECH 2000 high performance protective oil is a special long-time synthetic lubricant which contains high-quality corrosion inhibitor additives. The excellent lubrication and protection provided by the product perfectly responds to high industrial requirements. The oily protective film builds a water-repellent, anticorrosive layer, applicable on any type of machine, tool or various other metal surfaces or components.

STALOC KORROTECH 2000 high performance protective oil has excellent capabilities regarding the protection and maintenance of weapons and guns, which provides for an extended lifetime and a safe use of weapons and other military components. The excellent creep capabilities of the product ensure a deep penetration and a safe protection and maintenance process.

STALOC KORROTECH 2000 high performance protective oil protects stored parts up to one year.

APPLICATION

Recommended application – further information can be found in the material safety data sheet.

Apply STALOC KORROTECH 2000 high performance protective oil and provide for enough penetrating time after application. Spray STALOC KORROTECH 2000 onto the substrate from a distance of 25-30cm.

Highest effectiveness directly after application!

GENERAL PROPERTIES

- outstanding lubrication and protection properties
- water repellent and corrosion inhibiting film with outstanding creep properties
- excellent protection for weapons
- protects from corrosion for up to 1 year
- 360° spray valve

TECHNICAL PROPERTIES

ATTRIBUTE	UNIT	SPECIFICATION
colour		transparent / brown
basis		synthetic oil / paraffine
temperature resistance	°C	-40°C to 180°C
application temperature	°C	+10°C to 35°C
odour		wintergreen
density at 20°C	g/ml	0,670 – 0,700 g/ml
resistant against		weak acids and bases atmospheric exposure
shelf life at +25°C	years	10 years

SAFETY INFORMATION

Please send your request for the latest version of the material safety data sheet (MSDS).



PACKAGING / VOLUME

400 ml 520 3e à 12 pcs per box

5 l / 20 l / 180 l container

The information and data in this document are for information purposes only. STALOC cannot take responsibility for the results obtained by a third party, whose methods are not under STALOC control. The determination of the suitability for the user's purpose of any STALOC product is the responsibility of the client. Consequently, STALOC recommends testing of the products before using it for a series application. Moreover, it is the responsibility of the customer to ensure a safe environment for the user. STALOC therefore disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of STALOC products. STALOC cannot be held liable for any consequential or incidental damage resulting from the use of a STALOC product, including lost profits or damages of any other kind. Products or processes mentioned herein might be subject to released or pending patents or licences.

Issued: 04.05.2012



call STALOC



www.staloc.com

